




















































































































ردیف	مدل	مشخصات فنی	تصویر	قیمت مصرف کننده (ریال)
IP Camera				
1	SM-IP2910D-WF 	Wi-Fi PT Camera Up to 30m (based on actual environment) 1/3" CMOS Sensor/ 2MP(25FPS) /4 mm fixed Lens/2Stream/S+265/H.265 DWDR/ 10m White light view distance; 20m IR view distance/ 0.02Lux@F2.0/ IR-cut filter with auto switch (ICR) 3D DNR, HLC, BLC,AWB,AGC, Defog,Privacy Mask/ANR Smart IR, Surge Protection / 5VDC, Built-in Mic, Built-in Speaker, SD Card Max 512GB, Auto Tracking 1*RJ-45 (10/100 Base-T)/ONVIF/Reset Button/P2P/Plastic		78,000,000
2	SM-IP2441P2S1-WS 	1/2.9" CMOS Sensor/2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Super Starlight /15m White light view distance/ 0.0002Lux@ F1.0 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm(SMD1.0)		133,000,000
3	SM-IP2531P2S1-WS 	1/2.9" CMOS Sensor/2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Super Starlight /15m White light view distance/ 0.0002Lux@ F1.0 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P IP66 (Metal+ Plastic) Video Analytics: Smart Alarm(SMD1.0)		133,000,000
4	SM-IP2D2020	2MP IR Omni Camera 1/3" CMOS Sensor/ 2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/ 50m IR view distance/ 0.02Lux@ F1.6 /Smart IR / built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/ Motion detection/ Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P IP67 Plastic		156,000,000
5	SM-IP2400D1 	1/3" CMOS Sensor/ 2MP(25FPS) / 4 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6/Smart IR / built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Motion detection 1*RJ-45 (10/100 Base-T),POE/ONVIF/Surge Protection IP67 Plastic		63,000,000
6	SM-IP2500D1 	1/3" CMOS Sensor/ 2MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6/Smart IR / built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Motion detection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/Surge Protection/ Plastic		63,000,000
7	SM-IP4441T2S1(2.8) 	1/3" CMOS Sensor/4MP(25FPS) /2.8mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm(human and vehicle detection)SMD1.0		116,000,000






























8	<p>SM-IP4441T2S1(4)</p>  <p>Smart Dual Light</p>	<p>1/3" CMOS Sensor/4MP(25FPS) /4mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm(human and vehicle detection)SMD1.0</p>	  	115,000,000
9	<p>SM-IP4531T2S1</p>  <p>Smart Dual Light</p>	<p>1/3" CMOS Sensor/4MP(25FPS) /2.8mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/ 3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/P2P IP66 (Metal+ Plastic) Video Analytics: Smart Alarm(human and vehicle detection)SMD1.0</p>	  	115,000,000
10	<p>SM-IP6441T2S1</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/6MP(25FPS) /2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/P2P IP67 (Metal+ Plastic) Video Analytics: Smart Alarm(human and vehicle detection)SMD1.0</p>	  	160,000,000
11	<p>SM-IP6531T2S1</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/6MP(25FPS) /2.8 mm fixed Lens/2Stream/S+265/H.265/ DWDR/15m White light view distance; 30m IR view distance/ 0.02Lux@ F1.6 /Smart IR/ built-in MIC/3D DNR, HLC, BLC,AWB,AGC, Defog/Privacy Mask/Surge Protection 1*RJ-45 (10/100 Base-T) ,POE/ONVIF/P2P IP66 (Metal+ Plastic) Video Analytics: Smart Alarm(human and vehicle detection)SMD1.0</p>	  	160,000,000
12	<p>SM-IP5441T3S2-WS</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/15m White light distance; 50m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC, ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	 <p>True WDR Starlight</p>   	191,000,000
13	<p>SM-IP5482T3S2-WS</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 15m White light distance; 80m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC, ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	 <p>True WDR Starlight</p>   	240,000,000
14	<p>SM-IP5531T3S2-WS</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 15m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC, ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	 <p>True WDR Starlight</p>   	192,500,000
































15	<p>SM-IP5531T3S2-WSI</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.8 mm fixed Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 10m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67,IK10 (Metal+Plastic) Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	  	193,500,000
16	<p>SM-IP5482T3S2Z-WS</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.7~13.5mm Motorized Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 15m White light distance; 80m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	  	315,000,000
17	<p>SM-IP5572T3S2Z-WSI</p>  <p>Smart Dual Light</p>	<p>1/2.7" CMOS Sensor/ 5MP(25FPS) / 2.7~13.5mm Motorized Lens/2Stream/S+265/H.265/ True WDR 120dB/Starlight/ 10m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67,IK10 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	  	315,000,000
18	<p>SM-IP8442T3S2-WS</p>  <p>Smart Dual Light</p>	<p>1/2.8" CMOS Sensor/ 8MP(20FPS) / 2.8 mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 50m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	  	280,000,000
19	<p>SM-IP8532T3S2-WS</p>  <p>Smart Dual Light</p>	<p>1/2.8" CMOS Sensor/ 8MP(20FPS) / 2.8 mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	  	280,000,000
20	<p>SM-IP8482T3S2Z-WS</p>  <p>Smart Dual Light</p>	<p>1/2.8" CMOS Sensor/ 8MP(20FPS) / 2.7~13.5mm Motorized Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 80m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC/ ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 Metal Video Analytics: SMD2.0 (Human/Vehicle Classification);Tripwire,Perimeter</p>	  	Call

21	<p>SM-IP4481D4SZ-WSLR(2.8-12)</p>   <p>Dual Light</p>	<p>4MP LPR Network Camera 1/1.8" CMOS Sensor/ 4MP(25FPS) / 2.8~12mm Motorized Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 40m White light distance; 30m IR distance/ 0.002Lux@ F1.3~F2.2 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 2/1, RS485, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Pro)- Supports license plate recognition- Early Warning(EW)- SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight LPR</p>   	Call
22	<p>SM-IP4481D4SZ-WSLR(8-32)</p>   <p>Dual Light</p>	<p>4MP LPR Network Camera 1/1.8" CMOS Sensor/ 4MP(25FPS) / 8~32mm Motorized Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 60m White light distance; 60m IR distance/ 0.002Lux@ F1.6~F1.7 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 2/1, RS485, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Pro)- Supports license plate recognition- Early Warning(EW)- SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight LPR</p>   	Call
23	<p>SM-IP5481D4S-WST</p>   <p>Dual Light</p>	<p>5MP Thermal Network Camera 1/2.7" CMOS Sensor/Optical:5MP(25FPS) ,Thermal:720P Thermal:7mm;Optical:6mm fixed Lens/ 2Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 50m IR distance/ 0.002Lux@Thermal:F1.2; Optical:F1.6 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 2/1, RS485, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Lite) -Thermal SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight Fire Detection</p>   	Call
24	<p>SM-IP5442D4S-WSFC</p>   <p>Dual Light</p>	<p>5MP Face Capture Network Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) / 1080P 50fps 4mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 50m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 Metal SMART Functions(Lite)- Face Capture- Early Warning(EW) SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight Face Capture</p>   	295,000,000
25	<p>SM-IP5532D4S-WSFC</p>   <p>Dual Light</p>	<p>5MP Face Capture Network Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) / 1080P 50fps 2.8mm fixed Lens/3Stream/S+265/H.265/Motion JPEG True WDR 120dB/Starlight/ 15m White light distance; 30m IR distance/ 0.002Lux@ F1.6 /Smart IR/ built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection/ Corridor Mode 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP66 Metal SMART Functions(Lite)- Face Capture- Early Warning(EW) SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight Face Capture</p>   	295,000,000

26	<p>SM-IP8481P4S-WSP</p> <p>PRO  Polar Day</p>	<p>8MP Polar day Panoramic Network Camera Dual 1/2.7" CMOS Sensor/ 8MP(25FPS) 2.8mm fixed Lens/2Stream/S+265/H.265/Motion JPEG True WDR 120dB/Super Starlight/ 15m White light distance/ 0.0001Lux@ F1.0 /built-in MIC & Speaker ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog/Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, Support Micro SD Card up to 512GB, IP67 (Metal+Plastic) SMART Functions(Lite)- Early Warning(EW) SMD (Human/Vehicle Classification)</p>	 <p>True WDR Super starlight Panoramic</p> <p>SMD </p>	515,000,000
27	<p></p> <p>SM-IP842PH-SFR</p> <p>PRO IR</p>	<p>8MP 180° Panoramic Network Camera 1/2.8" SONY(4pcs*2MP) progressive scan CMOS Sensor / 8MP(4096 x 1800) (25FPS) 3.2mm fixed Lens x 4 /3Streams/H.265+/H.264+ DWDR/ Starlight/ 20m IR/ 0.008 lux/ 12V DC/ PoE/ ONVIF 1/1 CH Audio In/Output , 1/1 CH Alarm In/Output, SD Card Max 256GB, RS485 3D DNR, HLC, BLC, defog, EIS, IP67, IK10 SMART Functions / Supports face detection and comparison</p>	 <p>Face Recognition Starlight</p> <p>Panoramic </p>	585,000,000
28	<p>SM-IPS27MFP</p> <p>PRO  Dual Light</p>	<p>Face Panel & Access Control Terminal Standalone/7 inch LCD screen/Face Liveness Detection 1/2.8" progressive scan CMOS Sensor/ 2MP(25FPS) 4.3 mm x 2 lens/3Streams/H265+/H264+/ WDR(72dB), 3D DNR, HLC, BLC, defog, DC12V/1A Face Recognition Distance: 1.5m Face Picture Database: 10,000 White Light Distance: 1m soft light IR Light Distance: 2m 1 Built-in MIC/Built-in Speaker - 1/1 CH Alarm In/Output 1CH RJ45-1CH Wiegand-1CH Lock-1CH Door contact input-Exit Buttonx1-Tamper Buttonx1-Built-in card reader door opening modes (Only card, Only face recognition, card and face recognition, card Or face recognition) Card Type: Mifare Card/Desfire Card/FM1208 Card/Gicard SMART Functions /Supports face detection and comparison</p>	 <p>Card Reader Door Control</p> <p>Face Recognition </p>	130,000,000
29	<p>SM-IP2641S4-23X-WS</p> <p>PRO IR</p>	<p>2MP 23X IR PTZ Camera 1/2.8" CMOS Sensor/ 2MP(25FPS) /5mm~115mm Motorized Lens/3Stream/23X Optical Zoom/S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 150m IR view distance/ 0.001Lux@ F1.5~F3.0 /Smart IR ROI, 3D DNR, HLC, BLC, AWB, AGC,ANR, Defog, Demist/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P, SD Card Max 512GB/ Power-off Memory/ IP66 (Metal+plastic) Video Analytics: Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing;Heatmap; Video Abnormal; SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight</p>	635,000,000
30	<p>SM-IP4642S4-25X-WSFC</p> <p>PRO IR</p>	<p>4MP Face Capture 25X IR PTZ Camera 1/2.7" CMOS Sensor/ 4MP(25FPS) /4.8mm~120mm Motorized Lens/ 3Stream/ 25X Optical Zoom/ S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 150m IR view distance/ 0.001Lux@ F1.67~F3.67 /Smart IR ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, SD Card Max 512GB/ Power-off Memory/ IP66 Metal SMART Functions(Pro)- Face Capture- Auto-Tracking SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight</p> <p>Auto Tracking Face Capture</p>	1,160,000,000

31	<p>SM-IP5641S4-23X-WSFC</p> <p>PRO IR</p>	<p>5MP Face Capture 23X IR PTZ Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) /5mm~115mm Motorized Lens/3Stream/23X Optical Zoom/S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 150m IR view distance/ 0.001Lux@ F1.67~F3.67 /Smart IR ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/12VDC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 1/1, SD Card Max 512GB/ Power-off Memory/ IP66 (Metal+Plastic) SMART Functions(Pro)- Face Capture SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight Face Capture</p>	990,000,000
32	<p>SM-IP5662S4-30X-WSFC</p> <p>PRO IR</p>	<p>5MP Face Capture 30X IR PTZ Camera 1/2.7" CMOS Sensor/ 5MP(25FPS) /4.7mm~141mm Motorized Lens/ 3Stream/ 30X Optical Zoom/S+265/H.265/Motion JPEG True WDR 120dB/ Starlight/ 200m IR view distance/ 0.001Lux@ F1.6~F4.3 /Smart IR ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Privacy Mask/ Surge Protection/ Motion Detection 1*RJ-45 (10/100 Base-T) ,POE/24V:AC&DC/ONVIF/P2P Audio I/O: 1/1, Alarm I/O: 8/2, RS-485, SD Card Max 512GB/ Power-off Memory/ IP66 Metal SMART Functions(Pro)- Face Capture- Auto-Tracking SMD (Human/Vehicle Classification)</p>	 <p>True WDR Starlight Auto Tracking Face Capture</p>	Call
33	<p>SM-IP6P4661D4S-25X-WSFC</p> <p>PRO Polar Day</p>	<p>6MP 25X Polar Day Panoramic AEW PTZ Camera Panorama: 1/1.8" CMOS Sensor/6MP(25FPS)/2.8mm fixed Lens/2Streams/DWDR,Super starlight/30m White light distance/0.0001lux @ F1.0 Detail: 1/2.7" CMOS Sensor/4MP(25FPS)/4.8mm~120mm Motorized Lens/3Streams/25X Optical Zoom/ True WDR 120dB/ Starlight/30m White light distance; 150m IR distance/0.001Lux@ F1.67~F3.67 S+265/H.265/Motion JPEG/ ROI, 3D DNR, HLC, BLC,AWB,AGC, ANR, Defog, Demist/ Smart IR/ Privacy Mask/ Surge Protection/ Motion Detection/ 1*RJ-45 (10/100/1000 Base-T) ,POE/24V:AC&DC/ONVIF/P2P built-in Speaker, Audio I/O: 1/1, Alarm I/O: 2/1, SD Card Max 512GB/ Power-off Memory/ IP66 (Metal+plastic) SMART Functions(Pro)- Face Capture- Auto-Tracking- Auto Early Warning(AEW) SMD (Human/Vehicle Classification)</p>	 <p>True WDR AEW Super starlight Panoramic Face Capture</p>	Call
		NVR		
34	<p>SM-NS4106-4PE</p>	<p>4CH input - Record 6MP@25fps - 4*100M RJ45 PoE ports S+265,H.265,S+264 Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ SATA x 1, max 6T / HDMI-VGA/USB2.0x2/P2P/ ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps x 1,cloud upgrade Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>		108,500,000
35	<p>SM-NS8106-8PE</p>	<p>8CH input - Record 6MP@25fps - 8*100M RJ45 PoE ports S+265 ,H.265,S+264 Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ SATA x 1, max 6T / HDMI-VGA/USB2.0x2/P2P/ ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps x 1,cloud upgrade Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>		138,000,000
36	<p>SM-NL10106-8PE</p>	<p>10CH input - Record 6MP@25fps - 8*100M RJ45 PoE ports S+265,H.265,S+264 Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ SATA x 1, max 6T / 4K HDMI-VGA; USB2.0x2/P2P/ ONVIF/RSTP/DHCP/DDNS/ RJ45 100Mbps x 1,cloud upgrade Motion Detection قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>		145,000,000

37	SM-NM5108	<p>5CH input - Record 8MP@25fps /S+265,H.265,S+264/ Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/SATA × 1, max 8T / 4K HDMI-VGA/USB2.0x2/P2P/ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Human/Vehicle Classification <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	  	100,000,000
38	SM-NM10108	<p>10CH input - Record 8MP@25fps /S+265,H.265,S+264/ Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/SATA × 1, max 8T / 4K HDMI-VGA/USB2.0x2/P2P/ONVIF/RTSP/DHCP/DDNS/ RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Human/Vehicle Classification <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	  	112,000,000
39	SM-NM10118	<p>10CH input - Record 8MP@25fps /S+265,H.265,S+264/ Bandwidth (Input 60Mbps/Output 40Mbps) Support IPC Alarm input/ 1-RCA Audio Output / SATA × 1, max 10T / 4K HDMI-VGA/USB2.0x2/P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Human/Vehicle Classification <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	  	155,000,000
40	SM-NM20118S	<p>20CH input - Record 8MP@25fps / S+265,H.265,S+264/ Bandwidth (Input 100Mbps/Output 80Mbps) Support IPC Alarm input/ 1-ch Audio Output / SATA × 1, max 10T/ 4K HDMI-VGA /USB2.0x2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera); Supports People Counting; Face Detection (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	    	206,000,000
41	SM-NM101216AI	<p>10CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth (Input 100Mbps/Output 80Mbps) Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 1, max 10T/ 4K HDMI-VGA /USB2.0x2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR); Supports People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	    	230,000,000
42	SM-NM201216AI	<p>20CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth (Input 100Mbps/Output 80Mbps) Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 1, max 10T/ 4K HDMI-VGA /USB2.0x2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR); Supports People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	    	255,000,000
43	SM-NM202216AI	<p>20CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 160Mbps(AI on:120Mbps)/Output 80Mbps Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 2, max 10T/ 4K HDMI-VGA /USB2.0x2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 100Mbps × 1, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR); Supports People Counting; Face Recognition (Gender;Age; Glasses;Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD <i>قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</i></p>	    	412,000,000

44	<p>SM-NM322216AI</p>	<p>32CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 160Mbps(AI on:120Mbps)/Output 80Mbps Support Alarm I/O: 4Ch input,1Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 2, max 10T/ 4K HDMI-VGA /USB2.0*2/ P2P/ ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 1, cloud upgrade SMART Function(AI by Camera & NVR): Supports People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	   	488,000,000
45	<p>SM-NH402216AI</p> <p>PRO</p>	<p>40CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 200Mbps)/ Output 400Mbps(AI on: 200Mbps) Support Alarm I/O: 16Ch input,4Ch Output/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 2, max 10T/ 4K HDMI-VGA /1xUSB2.0; 1xUSB3.0/ RS485x1 / RS232x1/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	     	800,000,000
46	<p>SM-NH404216AI</p> <p>PRO</p>	<p>40CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 200Mbps)/ Output 400Mbps(AI on: 200Mbps) Support IPC Alarm input/ Audio I/O: 1-ch input,1-ch RCA Output SATA × 4, max 10T/ Support RAID0, RAID1, RAID5, RAID6, RAID10/ 4K HDMI-VGA /1xUSB2.0; 1xUSB3.0/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	      	950,000,000
47	<p>SM-NH408216AI</p> <p>PRO</p>	<p>40CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 320Mbps)/ Output 400Mbps(AI on: 200Mbps) Support Alarm I/O: 16Ch input,4Ch Output/ Audio I/O: 1-ch input,1-ch BNC Output SATA × 8, max 24T; 1xeSATA/ Support RAID0, RAID1, RAID5, RAID6, RAID10, RAID50, RAID60 / 4K HDMix2-VGAx2/ 2xUSB2.0; 1xUSB3.0/ RS485x2 / RS232x1/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender; Age; Glasses; Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	      	Call
48	<p>SM-NH808216AI</p> <p>PRO</p>	<p>80CH input - Record 16MP@25fps / S+265,H.265,S+264/ Bandwidth: Input 400Mbps(AI on: 320Mbps)/ Output 400Mbps(AI on: 200Mbps) Support Alarm I/O: 16Ch input,4Ch Output/ Audio I/O: 1-ch input,1-ch BNC Output SATA × 8, max 24T; 1xeSATA/ Supports RAID0, RAID1, RAID5, RAID6, RAID10, RAID50, RAID60 / 4K HDMix2- VGAx2 / 2xUSB2.0; 1xUSB3.0/ RS485x2 / RS232x1/ P2P/ONVIF/RTSP/DHCP/DDNS RJ45 1000Mbps × 2, cloud upgrade- Dual Stream Record SMART Function(AI by Camera & NVR): Supports License Plate Recognition; People Counting; Face Recognition (Gender;Age;Glasses;Face Mask; Body Temp); Fire Detection; Temperature Measurement; Human/Vehicle Classification; SMD قابلیت پشتیبانی از تقویم شمسی و منوی فارسی</p>	      	Call

کلیه محصولات لیست با گارانتی شرکت سیماران می باشند